


Blanker Keilstahl

Acier étiré a clavettes / Cold drawn key steel

in Güte C 45 scharfkantig gezogen nach DIN 6680 – EN 10277/10278
in Stablängen von 3 bis 3,50 Meter

	kg/m		kg/m		kg/m
 <p>Stahl- und Buntmetallhandel</p>	0,126	• 14 x 9 mm	0,99	• 25 x 14 mm	2,75
	1,196	• 14 x 14 mm	1,54	• 25 x 25 mm	4,91
	0,188	• 15 x 15 mm	1,65	• 28 x 16 mm	3,52
	0,283	• 16 x 7 mm	0,88	• 30 x 30 mm	7,07
• 7 x 7 mm	0,385	• 16 x 10 mm	1,26	• 32 x 18 mm	4,52
• 8 x 5 mm	0,314	• 16 x 12 mm	1,51	• 36 x 20 mm	5,65
• 8 x 7 mm	0,440	• 16 x 16 mm	2,01	• 40 x 22 mm	6,91
• 8 x 8 mm	0,502	• 18 x 7 mm	0,99	• 45 x 25 mm	8,83
• 10 x 6 mm	0,471	• 18 x 11 mm	1,55	• 50 x 28 mm	10,09
• 10 x 8 mm	0,628	• 18 x 18 mm	2,54	• 56 x 32 mm	14,06
• 10 x 10 mm	0,785	• 20 x 8 mm	1,26	• 63 x 32 mm	15,83
• 12 x 6 mm	0,565	• 20 x 10 mm	1,57	• 70 x 36 mm	19,78
• 12 x 8 mm	0,754	• 20 x 12 mm	1,88	• 80 x 40 mm	25,1
• 12 x 10 mm	0,942	• 20 x 20 mm	3,14	• 90 x 45 mm	28,3
• 12 x 12 mm	1,13	• 22 x 14 mm	2,42	• 100x 50mm	39,2
• 14 x 6 mm	0,66	• 22 x 22 mm	3,80		

Keilstähle in Sondermaßen und Zollabmessungen beschaffen wir auf Anfrage.