



Blanker Automaten-Rundstahl

Ronds étirés de décolletage /
Cold drawn free cutting rounds

nach **EN 10277**

Toleranzen nach DIN 668 /671 – **EN 10278**

Stablänge ca. 3 Meter

| Ø | kg/m | 11 S Mn 30 | 11 S Mn Pb 30 |
|---------|-------|------------|---------------|
| 2,0 mm | 0,025 | • | • |
| 3,0 mm | 0,056 | • | • |
| 3,5 mm | 0,076 | | • |
| 4,0 mm | 0,099 | • | • |
| 4,5 mm | 0,125 | | • |
| 5,0 mm | 0,154 | • | • |
| 5,5 mm | 0,187 | | • |
| 6,0 mm | 0,222 | • | • |
| 6,5 mm | 0,261 | | • |
| 7,0 mm | 0,302 | • | • |
| 7,5 mm | 0,347 | | • |
| 8,0 mm | 0,395 | • | • |
| 8,5 mm | 0,446 | | • |
| 9,0 mm | 0,499 | • | • |
| 9,5 mm | 0,556 | | • |
| 10,0 mm | 0,617 | • | • |
| 10,5 mm | 0,677 | | • |
| 11,0 mm | 0,746 | • | • |
| 12,0 mm | 0,888 | • | • |
| 12,5 mm | 0,963 | | • |
| 13,0 mm | 1,042 | • | • |
| 14,0 mm | 1,208 | • | • |
| 14,5 mm | 1,296 | | • |
| 15,0 mm | 1,387 | • | • |
| 15,5 mm | 1,481 | | • |
| 16,0 mm | 1,58 | • | • |
| 16,5 mm | 1,68 | | • |
| 17,0 mm | 1,78 | • | • |
| 17,5 mm | 1,89 | | • |
| 18,0 mm | 2,00 | • | • |
| 18,5 mm | 2,11 | • | • |
| 19,0 mm | 2,23 | • | • |
| 19,5 mm | 2,34 | • | • |
| 20,0 mm | 2,47 | • | • |
| 21,0 mm | 2,72 | • | • |
| 22,0 mm | 2,98 | • | • |
| 23,0 mm | 3,26 | • | • |
| 24,0 mm | 3,55 | • | • |
| 24,5 mm | 3,70 | | • |
| 25,0 mm | 3,85 | • | • |
| 26,0 mm | 4,17 | • | • |
| 27,0 mm | 4,50 | • | • |
| 28,0 mm | 4,83 | • | • |
| 29,0 mm | 5,19 | • | |
| 30,0 mm | 5,55 | • | • |