



Blanker Automaten-Sechskantstahl

Hexagones étirés de décolletage
Cold drawn free cutting hexagons

nach **EN 10277/10278**

Stablänge ca. 3 bis 3,50 Meter

	Abmessung	kg/m	11 S Mn 30	11 S Mn Pb 30
SW	5,0 mm	0,17	•	•
	5,5 mm	0,21		•
	6,0 mm	0,25	•	•
	7,0 mm	0,33	•	•
	8,0 mm	0,44	•	•
	9,0 mm	0,55	•	•
	10,0 mm	0,68	•	•
	11,0 mm	0,82	•	•
	12,0 mm	0,98	•	•
	13,0 mm	1,15	•	•
	14,0 mm	1,33	•	•
	16,0 mm	1,74		•
	17,0 mm	1,96	•	•
	18,0 mm	2,20	•	•
	19,0 mm	2,45	•	•
	22,0 mm	3,29	•	•
	24,0 mm	3,91	•	•
	27,0 mm	4,96	•	•
	30,0 mm	6,12	•	•
	32,0 mm	6,96	•	•
	36,0 mm	8,81	•	•
	38,0 mm	9,82		•
	41,0 mm	11,4	•	•
	46,0 mm	14,4	•	•
	50,0 mm	17,0	•	•
	55,0 mm	20,6	•	•
	60,0 mm	24,5	•	•
	65,0 mm	28,7	•	•
	70,0 mm	33,3	•	•
	75,0 mm	38,3	•	•
	80,0 mm	43,5	•	•
	85,0 mm	49,1	•	
	90,0 mm	55,1	•	
	100,0 mm	68,0	•	

Auf Wunsch gefasst von 10 – 50mm.