

Rundrohre


Tubes ronds / Round tubes

AlMgSi 0,5 F 22

EN 573-3 / 755-1,2,7,9

EN AW-6060 T66 gepresst

Herstellungslängen ca. 6 Meter



Abmessung d x s in mm	Gewicht kg/m	Abmessung d x s in mm	Gewicht kg/m	Abmessung d x s in mm	Gewicht kg/m	Abmessung d x s in mm	Gewicht kg/m
50 x 4,0	• 1,618	66 x 3,0	• 1,662	90 x 5,0	• 3,797	125 x 5,0	• 5,090
50 x 5,0	• 1,978	70 x 2,0	• 1,196	90 x 10,0	• 7,034	130 x 3,0	• 3,350
50 x 6,0	• 2,281	70 x 3,0	• 1,767	95 x 5,0	• 3,888	130 x 5,0	• 5,399
50 x 10,0	• 3,517	70 x 4,0	• 2,322	100 x 2,0	• 1,723	133 x 3,0	• 3,429
54 x 2,0	• 0,915	70 x 5,0	• 2,857	100 x 2,5	• 2,143	140 x 4,0	• 4,714
55 x 2,0	• 0,932	70 x 10,0	• 5,275	100 x 3,0	• 2,558	140 x 5,0	• 5,935
55 x 2,5	• 1,154	75 x 2,5	• 1,594	100 x 4,0	• 3,376	150 x 3,0	• 3,877
55 x 5,0	• 2,198	75 x 5,0	• 3,077	100 x 5,0	• 4,176	150 x 5,0	• 6,374
56 x 3,0	• 1,400	76 x 2,5	• 1,616	100 x 10,0	• 7,913	150 x 10,0	• 12,309
58 x 3,0	• 1,451	76 x 3,0	• 1,925	105 x 2,5	• 2,174	156 x 3,0	• 4,036
60 x 1,5	• 0,771	80 x 2,0	• 1,372	106 x 3,0	• 2,717	160 x 4,0	• 5,486
60 x 2,0	• 1,020	80 x 2,5	• 1,703	108 x 3,0	• 2,750	160 x 5,0	• 6,814
60 x 2,5	• 1,264	80 x 3,0	• 2,031	108 x 4,0	• 3,657	170 x 5,0	• 7,265
60 x 3,0	• 1,506	80 x 4,0	• 2,673	110 x 3,0	• 2,822	180 x 5,0	• 7,730
60 x 4,0	• 1,969	80 x 5,0	• 3,297	110 x 5,0	• 4,616	200 x 5,0	• 8,752
60 x 5,0	• 2,418	80 x 10,0	• 6,154	110 x 10,0	• 8,792	206 x 3,0	• 5,360
60 x 6,0	• 2,849	84 x 2,0	• 1,442	115 x 5,0	• 4,840	210 x 5,0	• 9,102
60 x 10,0	• 4,396	85 x 5,0	• 3,517	120 x 3,0	• 3,086	250 x 5,0	• 9,604
65 x 2,0	• 1,108	86 x 3,0	• 2,189	120 x 4,0	• 4,079		
65 x 2,5	• 1,374	90 x 2,0	• 1,547	120 x 5,0	• 5,055		
65 x 5,0	• 2,638	90 x 3,0	• 2,295	120 x 8,0	• 7,878		

Rundrohre

AlCuMgPb, F34-38

EN 573-3 / 754-1,2,7,8 / 755-1,2,7,8

EN-AW-2007 gezogen, gepresst

Herstellungslängen ca. 3 Meter

Abmessung d x s in mm	Gewicht kg/m	Abmessung d x s in mm	Gewicht kg/m	Abmessung d x s in mm	Gewicht kg/m	Abmessung d x s in mm	Gewicht kg/m
20/5	• 0,648	50/15	• 4,536	70/20	• 8,693	120/10	• 9,503
30/5	• 1,080	60/5	• 2,376	80/10	• 6,047	120/15	• 13,607
40/5	• 1,512	60/8	• 3,594	80/15	• 8,423	120/20	• 17,278
40/8	• 2,212	60/10	• 4,320	80/20	• 10,367	150/10	• 12,815
40/10	• 2,592	60/15	• 5,831	90/10	• 6,911	150/15	• 17,494
50/5	• 1,944	60/20	• 6,911	100/10	• 7,775	150/20	• 22,462
50/8	• 2,903	70/10	• 5,183	100/15	• 11,015	200/10	• 16,414
50/10	• 3,456	70/15	• 7,127	100/20	• 13,823		

Weitere Abmessungen aus Werksvorrat lieferbar. Auch in den Qualitäten AlMgSi 1, EN-AW 6082.